



Standard dimensioner

Höjd H: 96 – 1 008 mm
 Flänsbredd B: 55 – 500 mm
 Livtjocklek Tw: 5 – 30 mm
 Flänstjocklek Tf: 6 – 40 mm
 Standardlängd: 5000 – 12 000 mm

Balkstorlek	IPE-balk (DIN 1025-5)				
	H	B	Tw	Tf	r
100	100	55	5	6	5
160	160	82	5	8	5
200	200	100	5	8	5
240	240	120	6	10	6
300	300	150	8	10	6
360	360	170	8	12	6
400	400	180	8	12	7
450	450	190	10	15	7
500	500	200	10	15	7
550	550	210	10	20	9
600	600	220	12	20	9
700	-	-	-	-	-
800	-	-	-	-	-
900	-	-	-	-	-
1000	-	-	-	-	-

Balkstorlek	HEA-balk (DIN 1025-3)				
	H	B	Tw	Tf	r
100	96	100	5	8	5
160	152	160	6	8	5
200	190	200	6	10	6
240	230	240	8	12	6
300	290	300	8	15	7
360	350	300	10	20	7
400	390	300	12	20	9
450	440	300	12	20	9
500	490	300	12	25	9
550	540	300	12	25	11
600	590	300	12	25	11
700	690	300	15	25	11
800	790	300	15	30	11
900	890	300	15	30	14
1000	990	300	15	30	14

Balkstorlek	HEB-balk (DIN 1025-2)				
	H	B	Tw	Tf	r
100	100	100	6	10	5
160	160	160	8	12	6
200	200	200	8	15	7
240	240	240	10	20	7
300	300	300	10	20	9
360	360	300	12	25	11
400	400	300	12	25	11
450	450	300	15	25	11
500	500	300	15	30	11
550	550	300	15	30	11
600	600	300	15	30	14
700	700	300	20	30	14
800	800	300	20	35	14
900	900	300	20	35	14
1000	1000	300	20	35	14

Balkstorlek	HEM-balk (DIN 1025-4)				
	H	B	Tw	Tf	r
100	120	106	12	20	14
160	180	166	15	25	11
200	220	206	15	25	11
240	270	248	20	30	14
300	340	310	20	40	18
360	395	308	20	40	18
400	432	307	20	40	18
450	478	307	20	40	18
500	524	306	20	40	18
550	572	306	20	40	18
600	620	305	20	40	18
700	716	304	20	40	18
800	814	303	20	40	18
900	910	302	20	40	18
1000	1008	302	20	40	18